



NuCote™

FLOORING PERFECTION



Epoxy coatings are hard wearing systems which can provide elements such as chemical resistance with a seamless high-gloss finish for hygienic conditioning & easy cleaning.

EPOXY SCREEDS & COATINGS

EPOXY SCREEDS & COATINGS

Epoxy flooring can withstand harsh levels of wear & tear, for longer periods and are a popular flooring option in Industrial & Commercial workspaces. Our product range provides a smooth, easy to clean surface with excellent resistance to chemicals and abrasion.



HYGIENIC ENVIRONMENTS



IMPACT RESISTANT



EASY TO CLEAN & MAINTAIN



AESTHETIC & DECORATIVE

NuCote HB & SL Colour Range

LIGHT GREY

BASALT GREY

PEBBLE GREY

PLATINUM GREY

EMERALD GREEN

BEIGE

OYSTER WHITE



TRAFFIC BLACK

SKY BLUE



The colours printed will not match the final colour of the product or sample colours. There will be a slight colour variance. But NuCote™ strives to provide accurate colours at all times.

-  Residential Buildings
-  Industrial Industry
-  Commercial Industry
-  Retail & Leisure Outlets



NuCote Epoxy Coving Mortar

ADVANTAGES	FINISH	APPLICATION	PRODUCT COMPONENTS	RECOMMENDED USE
<p>Easy to Clean. High Abrasion Resistance. Solvent Free Seamless. Limited Pot Life. Fast Cure.</p>	 Textured Non-Hazardous	 Trowel Applied	<p style="text-align: center;">3</p> Part A - Base Part B - Hardener Part C - Aggregate	<p>Warehouses. Production Facilities. NuCote PU Range. High Impact Areas. Dairies Processing. Manufacturing Plant.</p>

NuCote HB

ADVANTAGES	FINISH	APPLICATION	PRODUCT COMPONENTS	RECOMMENDED USE
<p>Easy to Use. Good Abrasion Resistance. Solvent Free. Chemical Resistance. Non-Toxic. Resistant to Fungal Attack.</p>	 Smooth Seamless	 Roller Brush 200-300µm	<p style="text-align: center;">2</p> Part A - Base Part B - Hardener	<p>Tanks & Silo Coatings. Production Facilities. Floor & Wall Coatings. Water Containing Areas. Steel Pipe Coatings.</p>

NuCote Epoxy SL (1-2 mm)

ADVANTAGES	FINISH	APPLICATION	PRODUCT COMPONENTS	RECOMMENDED USE
<p>Good Abrasion Resistance. Good Adhesion to Concrete. Easily Applied on Floors. Solvent Free. Non-Toxic. Simplified Mixing. Non-Absorbing</p>	 Smooth Seamless	 Self-Levelling 1-2 mm	<p style="text-align: center;">3</p> Part A - Base Part B - Hardener Part C - Filler	<p>High Build Epoxy Coating. Production Facilities. Warehouses. Applied 1-2mm</p>



www.nucote.co.za

+27 (0) 11 421 0313



DISAVOWAL: The customer acknowledges and understands that after delivery, the goods will have left the control of Rigifoam (Pty) Ltd, and that the customer will be responsible for the unpacking of and connection/installation of the goods. The customer acknowledges that it is his/her further responsibility to ensure that a fully qualified and competent person is used to install the goods to ensure their effective operation. Failure by the customer to ensure the installation of the goods, according to the written instructions of the manufacturer and/or supplier, by a fully qualified and competent person, may result in the failure of the goods, injury, loss, or damages to the customer. Accordingly, and in this event, Rigifoam (Pty) Ltd accepts no responsibility for any loss or damages that might arise by reason of death or personal injury to any person engaged in the installation or use of the goods thereafter, subject to the provisions of the Consumer Protection Act 68 of 2008.