

Chief and a Martin

This durable flooring range delivers impressive performance benefits for hard-wearing surfaces. The ideal application for floors that are subjected to UV exposure and require an economical yet flexible system.

PU COATING SYSTEMS

1

PU COATING SYSTEMS

PU Coatings help protect substrates from a variety of environmental impacts causing defects. Our hard-wearing PU Coating Range has been formulated for old and new concrete making it the ideal coating for protecting floors against abrasion, corrosion and other deteriorating processes.



NuCote[™] UVC

NuCote[™] UVC is a twin pack, UV-stable polyurethane coating system versatile and easy-to-use. The coating is flexible, with good resistance to various chemicals and has excellent bond-strength onto concrete and many other surfaces. NuCote[™] UVC is used as a pigmented coating or as a clear coating to seal various cementitious materials and offers a high gloss or matt finish.

Advantages	Finish	Application	Components	Recommended Use
 High solids content Durable and flexible Excellent bonding properties Abrasion and impact resistant Easy application 			2	 Interior and external use Can be applied onto horizontal and vertical surfaces High traffic areas Chemical resistant
	Gloss or Matt	Roller Applied	Part A - Polyol	
	Clear or Colour Seal	Seamless	Part B - ISO	

- Estimated coverage: 8 10m² p/l (at 80µm WFT)
- Two to three coats are required
- Consult NuCote[™] Sales





RESIDENTIAL BUILDINGS

COMMERCIAL PROPERTIES

INDUSTRIAL SPACES

RETAIL AND LEISURE OUTLETS

NuCote[™] UVGuard

NuCote[™] UVGuard is a twin pack, UV-stable polyurethane coating system that offers a high gloss or matt finish. The coating is flexible and has good resistance to various chemicals. It has excellent bond strength onto concrete and various other surfaces. It is used as a coating to seal various cementitious materials. This coating is versatile and easy to use.

Advantages	Finish	Application	Components	Recommended Use
 Aliphatic (UV stable coating) Penetrates to substrate High solids content Durable and flexible Excellent bonding properties Abrasion and impact resistant Excellent coverage Easy application 	Gloss or Matt		2	 Interior and external use Can be applied onto horizontal and vertical surfaces High traffic areas Chemical resistant
	Clear or Colour Seal	Roller Applied Part A - Polyol		
	UV Stable	Seamless	Part B - ISO	

• Estimated coverage: 8-10m² p/l (at 80µm WFT)

- Two to three coats are required
- Consult NuCote[™] Sales.





www.nucote.co.za +27 (0)11 421 03013



WHICH COLOUR IS BEST FOR YOU?

EXPLORE THE POSSIBILITIES

using our colour picker on our website

www.nucote.co.za

Proudly brought to you by



PPPPP

A CONTRACTO

DISAVOWAL: The customer acknowledges and understands that after delivery, the goods will have left the control of Rigifoam (Pty) Ltd, and that the customer will be responsible for the unpacking of and connection/installation of the goods. The customer acknowledges that it is his/her further responsibility to ensure that a fully qualified and competent person is used to install the goods to ensure their effective operation. Failure by the customer the installation of the goods, according to the written instructions of the manufacturer and/or supplier, by a fully qualified and competent person, may result in the failure of the goods, injury, loss, or damages to the customer. Accordingly, and in this event, Rigifoam (Pty) Ltd accepts no responsibility for any loss or damages that might arise by reason of death or personal injury to any person engaged in the installation or use of the goods thereafter, subject to the provisions of the Consumer Protection Act 68 of 2008.