



Durable Flooring Range, delivering impressive performance benefits for hard-wearing surfaces. Ideal application for floors subject to extreme temperatures & chemical exposure.




PU SCREED SYSTEMS

PU SCREED SYSTEMS




NuCote offers Durable Flooring Systems suitable for any environment. The PU Screed Range has been formulated to deliver the ultimate protection. It is designed to offer good chemical and impact resistance as well as thermal insulation, making our PU Screed Range the ideal application in both Industrial & Commercial buildings.






NuCote PU **HD** 6-9mm Screed

ADVANTAGES	FINISH	APPLICATION	NuCote HD COMPONENTS	RECOMMENDED PRODUCTS REQUIRED
Chemical & Abrasion Resistant Impact Resistant Temp Resistance -40 - 140°C Seamless Application Highly Trafficable Environmentally Friendly	 Textured / Matt Non-Hazardous Non-Slip	 Trowel Applied Easy Installation Seamless	 Part A - Resin Part B - Hardener Part C - Aggregate	NuCote Epoxy Paste NuCote Cleaner A & X NuCote MT / GP / PU Primer NuCote Lockcoat

NuCote PU **MD** 3-4mm Screed

ADVANTAGES	FINISH	APPLICATION	NuCote MD COMPONENTS	RECOMMENDED PRODUCTS REQUIRED
Chemical & Abrasion Resistant Impact Resistant Temp Resistance Seamless Application Trafficable Environmentally Friendly Flowable Self Smoothing	 Smooth Textured Non-Hazardous Non-Slip	 Self-Smoothing Easy Installation Seamless	 Part A - Resin Part B - Hardener Part C - Aggregate	NuCote Epoxy Paste NuCote Cleaner A & X NuCote MT / GP / PU Primer NuCote Lockcoat

NuCote PU **SL** 2mm Screed

ADVANTAGES	FINISH	APPLICATION	NuCote SL COMPONENTS	RECOMMENDED PRODUCTS REQUIRED
Chemical & Abrasion Resistant Impact Resistant Temp Resistance Seamless Application Trafficable Environmentally Friendly Flowable Self Levelling	 Smooth Textured Non-Hazardous Non-Slip	 Self-Levelling Easy Installation Seamless	 Part A - Resin Part B - Hardener Part C - Aggregate	NuCote Epoxy Paste NuCote Cleaner A & X NuCote MT / GP / PU Primer NuCote Lockcoat

WATCH POINTS

Humidity, moisture, and curing of the primers are essential to these systems. The Colours are not UV stable however, functional. They may discolour when exposed to direct sunlight or UV. Storage is also vital to ensure the materials remain in a workable condition.



Manufacturing Plants



Warehousing Facilities



Chemical Resistant Areas




Food & Beverage Processing

NuCote PU **UT** 4-5mm Screed

ADVANTAGES

Chemical & Abrasion Resistant
Impact Resistant
Heat Resistant To 80°C
Seamless Application
Anti-Microbial Silver Ion
Non-Slip Profiles
Flowable Self Levelling
Excellent Adhesion

FINISH



Various Broadcast
Non-Hazardous
Non-Slip

APPLICATION



Flowable
Easy Installation
Seamless

NuCote UT COMPONENTS

3

Part A - Resin
Part B - Hardener
Part C - Aggregate

RECOMMENDED PRODUCTS REQUIRED

NuCote Epoxy Paste
NuCote Cleaner A & X
NuCote MT / GP / PU
Primer
NuCote PU HD/MD/SL
NuCote Lockcoat

NuCote PU **Lockcoat** Over Coat

ADVANTAGES


Flowable, fast installation
Seamless & easy to clean
Compatible with PU Screeds
Chemical & Abrasion Resistant
Temp Resistance
Environmentally Friendly
System Overcoat

FINISH



Smooth / Textured
Non-Hazardous
Non-Slip / Smooth

APPLICATION



Roller
Easy Installation
Seamless

Lockcoat COMPONENTS

3

Part A - Resin
Part B - Hardener
Part C - Aggregate

RECOMMENDED PRODUCTS REQUIRED

NuCote Cleaner A & X
NuCote MT / GP / PU
Primer
NuCote PU HD/MD/SL

COLOURS RANGE





www.nucote.co.za

+27 (0) 11 421 0313



DISAVOWAL: The customer acknowledges and understands that after delivery, the goods will have left the control of Rigifoam (Pty) Ltd, and that the customer will be responsible for the unpacking of and connection/installation of the goods. The customer acknowledges that it is his/her further responsibility to ensure that a fully qualified and competent person is used to install the goods to ensure their effective operation. Failure by the customer to ensure the installation of the goods, according to the written instructions of the manufacturer and/or supplier, by a fully qualified and competent person, may result in the failure of the goods, injury, loss, or damages to the customer. Accordingly, and in this event, Rigifoam (Pty) Ltd accepts no responsibility for any loss or damages that might arise by reason of death or personal injury to any person engaged in the installation or use of the goods thereafter, subject to the provisions of the Consumer Protection Act 68 of 2008.