



# NuCote<sup>TM</sup>

FLOORING PERFECTION

Adhesion primer solutions  
formulated for excellent adherence  
to a variety of surfaces ensuring a good  
bond on to the substrate.

## NUCOTE PRIMERS

# NUCOTE PRIMERS



Light to Heavy  
Durability





Anti-Bacterial  
Properties





Impact  
Resistant



## NuCote™ GP Primer

Product Description	Parts	Application	Drying Time	Coverage
<ul style="list-style-type: none"> <li>• Cost-effective general-purpose primer</li> <li>• Epoxy-based for cementitious substrates</li> <li>• Solvent Free and low viscosity</li> <li>• Compatible with various floor systems</li> <li>• Coatings can be applied the next day</li> </ul>	2	 Squeegee or Roller	 <b>8 - 12 HOURS</b> TOUCH DRY	<b>4 m<sup>2</sup></b> PER LITRE Depending on wastage and surface profile



## NuCote™ MT Primer

Product Description	Parts	Application	Drying Time	Coverage
<ul style="list-style-type: none"> <li>• Good moisture-tolerant primer</li> <li>• Epoxy-based, cementitious and steel</li> <li>• Solvent-free and low viscosity</li> <li>• Compatible with various floor systems</li> <li>• Coatings can be applied the next day</li> </ul>	2	 Squeegee or Roller	 <b>8 - 12 HOURS</b> Touch Dry	<b>4 m<sup>2</sup></b> PER LITRE Depending on wastage and surface profile

## NuCote™ OT Primer

Product Description	Parts	Application	Drying Time	Coverage
<ul style="list-style-type: none"> <li>• Oil or grease contaminated substrates</li> <li>• Moisture tolerant epoxy-based</li> <li>• Eliminates out-gassing of concrete</li> <li>• Compatible with various floor systems</li> <li>• Coatings can be applied the next day</li> </ul>	2	 Squeegee or Roller	 <b>8 - 12 HOURS</b> Touch Dry	<b>4 m<sup>2</sup></b> PER LITRE Depending on wastage and surface profile

## NuCote™ RS Primer

Product Description	Parts	Application	Drying Time	Coverage
<ul style="list-style-type: none"> <li>• Rapid set epoxy primer</li> <li>• Epoxy-based, cementitious and steel</li> <li>• Solvent free and low viscosity</li> <li>• Compatible with various floor systems</li> <li>• Coatings can be applied the same day</li> </ul>	2	 Squeegee or Roller	 <b>1 - 2 HOURS</b> Touch Dry	<b>4 m<sup>2</sup></b> PER LITRE Depending on wastage and surface profile



# NuCote™

FLOORING PERFECTION



RESIDENTIAL BUILDINGS

COMMERCIAL PROPERTIES



INDUSTRIAL SPACES

RETAIL AND LEISURE OUTLETS



## NuCem™ Primer

Product Description	Parts	Application	Drying Time	Coverage
<ul style="list-style-type: none"><li>Water-based and cementitious substrates</li><li>Improves adhesion to concrete</li><li>Water resistant after film formation</li><li>Specific performance specifications</li><li>Easy-to-use with no restrictive pot life</li></ul>	1	 Brush or Roller	 2 - 4 HOURS Touch Dry	<b>10 m<sup>2</sup></b> PER LITRE Depending on wastage and surface profile



## NuCote™ PU Primer

Product Description	Parts	Application	Drying Time	Coverage
<ul style="list-style-type: none"><li>Polyurethane cement-based primer</li><li>Designed for use with NuCote™ Polyurethane screeds</li><li>Provides excellent bonding to both concrete substrates and the subsequent poly application on top</li></ul>	3	 Trowel or Squeegee	 8 - 12 HOURS Touch Dry	<b>4 m<sup>2</sup></b> PER LITRE Depending on wastage and surface profile

## NuCote™ WB Primer

Product Description	Parts	Application	Drying Time	Coverage
<ul style="list-style-type: none"><li>Water-based, high solids and cementitious substrates</li><li>Epoxy-based and highly breathable</li><li>Tolerant to applications over manually prepared substrates</li><li>Ideally suitable for substrates where primer breathability is required</li></ul>	2	 Brush or Roller	 4 - 6 HOURS Touch Dry	<b>8 m<sup>2</sup></b> PER LITRE Depending on wastage and surface profile

## NuCote™ SB Primer


Product Description	Parts	Application	Drying Time	Coverage
<ul style="list-style-type: none"><li>Solvent-based, low viscosity</li><li>Epoxy-based</li><li>Modified for deep penetration into concrete substrates</li><li>Enhanced with adhesion promoter for improved adhesion</li><li>Suitable for cementitious and resinous substrates</li></ul>	2	 Brush or Roller	 3 - 4 HOURS Touch Dry	<b>8-10 m<sup>2</sup></b> PER LITRE Depending on wastage and surface profile



[www.nucote.co.za](http://www.nucote.co.za)

+27 (0)11 421 03013



Proudly brought to you by  **RIGIfoam** (Pty) Ltd  
SUPERIOR PRODUCT

DISAVOWAL: The customer acknowledges and understands that after delivery, the goods will have left the control of Rigifoam (Pty) Ltd, and that the customer will be responsible for the unpacking of and connection/installation of the goods. The customer acknowledges that it is his/her further responsibility to ensure that a fully qualified and competent person is used to install the goods to ensure their effective operation. Failure by the customer to ensure the installation of the goods, according to the written instructions of the manufacturer and/or supplier, by a fully qualified and competent person, may result in the failure of the goods, injury, loss, or damages to the customer. Accordingly, and in this event, Rigifoam (Pty) Ltd accepts no responsibility for any loss or damages that might arise by reason of death or personal injury to any person engaged in the installation or use of the goods thereafter, subject to the provisions of the Consumer Protection Act 68 of 2008.